

Technical Data Sheet

BIVOS Oil Wax No. 375

Application range	In the interior, for the furniture care or final treatment of leached, oiled and waxed wood. Not for stained surfaces. For the restoration of old furniture or woodcarvings. For the care of KeraCott and linoleum floors.
Technical qualities	After drying velvet glossy and moisture-repellent surface. DIN EN 71 part 3 certified as suitable for toys.
Full declaration	Isoaliphates, linseed oil, linseed oil- stand oil - natural resin ester, linseed oil – stand oil, orange oil, beeswax, micronized wax, carnauba wax, pine oil, rosemary oil, ethanol, alumina, and drying agents free of lead (Co, Mn, Zr).
Color	Clear.
Dilution	Ready to use.
Application method	By spraying, with a wadded cloth or single disc rotary machine with felt pad.
Coverage	Exact coverage should be determined by doing a test application. 1 liter (1.06 quart) is sufficient for approximately 100 m ² (1076 ft ²), i.e. 10 ml/m ² , with other modes of application up to 167 m ² (1800 ft ²), i.e. 6 ml/m. Coverage could be considerably less, depending on the condition and absorbency of the surface.
Cleaning	Clean equipment immediately after use with SVALOS Thinner No. 222, or LEVO Brush Cleaner No. 997.
Drying time	When using a wadded cloth, approximately 20 – 30 minutes at 23 °C (73 °F) and 50% relative humidity. With a spraying device, the required drying time is 30 – 120 minutes depending on the application amount. All other application methods: 24 hours.
Specific gravity	0.84 g/ml.
Safety advice	<p>Ensure good ventilation during and after application. Always be sure to store and then dispose of cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with BIVOS Oil Wax No. 375 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content.</p> <p>The product itself will not combust spontaneously.</p> <p>P102 Keep out of reach of children. P301+P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor. EUH066 Repeated exposure may cause skin dryness or cracking. EUH208 Contains limonene, Cobalt (2+) salts. Can cause allergic reactions.</p>
Disposal	According to locally regulated laws.
Container size	0.05 l; 0.25 l; 0.75 l; 2.5 l; 10 l; 30 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years. Transfer unused portion of product to a smaller container for storage.
	See reverse for application instructions.

How to use

BIVOS Oil Wax No. 375

Preparation

The surface must be dry, solid, clean, and free of grease and dust.
Pretreat timber with LIVOS oils or stains like ARDVOS Universal Wood Oil No. 266, KUNOS Natural Oil Sealer No. 244 or DARIX Transparent Furniture Stain No. 297.

Application

Stir or shake product thoroughly before use. After a very thin application, there is no polishing necessary.

With other application methods such as spraying, pay careful attention to apply a very thin and even coat. Excess BIVOS Oil Wax No. 375 should be removed with a cloth. After 20 - 30 minutes of drying time, polish the surface with a brush, cloth or a single disc rotary machine with felt pad. 1 - 2 hours after polishing, the surface is dry to the touch.

Cleaning and Maintenance

Daily cleaning with TRENA pH-Neutral Cleaner No. 556 diluted with water. Clean heavily soiled surfaces with TRENA pH-Neutral Cleaner No. 556 or a saturated application of Oil Wax No. 375, which should left for about 20 minutes before taking off the dirt.
Treat with initial product; afterwards apply BIVOS Oil Wax No. 375 sparingly, if necessary several times.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

August 2015