


Technical Data Sheet

KUNOS Floor Maintenance No. 1862

Application range	In the interior, for maintaining wooden surface previously coated with KUNOS Natural Floor Sealer No. 242, KUNOS Natural Oil Sealer No. 244, ARDVOS Universal Wood Oil No. 266 or KOIMOS High Solid Parquet Oil NO. 277.
Technical qualities	Transparent, satin-glossy finish.
Full declaration	Linseed oil - stand oil - natural resin ester, isoaliphates, wood oil – stand oil, natural resin ester, dehydrated amino sugar and drying agents free of lead (Ca, Co, Mn, Zr).
Colors	Clear 002
Dilution	Ready to use.
Application method	With a lint-free cotton cloth or single disc rotary machine and felt pad, at temperatures above 15 °C (59 °F).
Coverage	6 ml/m ² . Coverage could be considerably less, depending on the absorbency and condition of the surface. Test application!
Cleaning	Clean equipment immediately after use with LEVO Brush Cleaner No. 997.
Drying time	At 23 °C (73 °F) and 50% relative humidity: 5 hours.
Specific gravity	Approximately 0.82 g/ml.
Safety advice	Provide enough ventilation after application.

Always be sure to store and then dispose of cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with KUNOS Floor Maintenance No. 1862 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content.

The product itself will not combust spontaneously.
Contains Cobalt (2+) salts. Can cause allergic reactions.



- | | |
|------|--|
| R 43 | May cause sensitisation by skin contact. |
| S 2 | Keep out of the reach of children. |
| S 24 | Avoid contact with skin. |
| S 37 | Wear suitable gloves. |
| S 62 | If swallowed do not induce vomiting; seek medical advice immediately and show this container or label. |

Disposal	According to locally regulated laws.
Container sizes	0.25 l; 5 l; 30 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years. Transfer unused product into a smaller container for storage in order to minimize excess air.

How to use

KUNOS Floor Maintenance No. 1862

- Preparation** The KUNOS surface to be treated must be dry, clean and free of dust.
- Application** Stir thoroughly before use. Remove possible skin formed on surface.
Test application!
Apply (approx. 5g/m²) KUNOS Floor Maintenance in drops onto the surface, and spread immediately using a single-disc machine with a felt pad or a lint-free cotton cloth. While polishing, try to avoid the formation of streaks. Check against the backlight. Repeat if necessary.
- Cleaning** Clean with TRENA pH-Neutral Cleaner No. 556 added to water, and wipe moist but not wet.
- Maintenance** Aftertreatment with KUNOS Floor Maintenance No. 1862 several times a year depending on the use.
- Important tips** If an abrasive pad is used with a single-disc machine to apply KUNOS Floor Maintenance, the color intensity of an existing pigmented coating or the surface layer may be decreased.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

November 2012