

## Technical Data Sheet

# GLEIVO Beeswax No. 315

<b>Application range</b>	For interior timber such as panelling and furniture that has been pre-treated with LIVOS oils or stains. Not suitable for areas exposed to water splashes. For regular maintenance of linoleum. To refresh waxed timber, cork and stone surfaces.
<b>Technical qualities</b>	Liquid. Applicable by airless spraying. Produces a satin glossy finish when completely dry.
<b>Full declaration</b>	Isoaliphates, beeswax, micronized wax, carnauba wax, linseed oil, orange oil, alumina, rosemary oil.
<b>Color</b>	Clear. Coloration is possible with max. 10% of VINDO Natural Gloss Paint No. 629
<b>Dilution</b>	Ready to use.
<b>Application method</b>	Apply a very thin coat by painting, spraying or with a wadded cloth at temperatures above 12 °C (54 °F).
<b>Coverage</b>	Treatment: 1 liter (1.06 quart) is sufficient for approximately 25 m <sup>2</sup> (269 ft <sup>2</sup> ), i.e. 40 ml/m <sup>2</sup> ; could be considerably less, depending on the condition and absorbency of the surface. Always do a test application! Maintenance: 1 liter (1.06 quart) is sufficient for an average of 100 m <sup>2</sup> (1076 ft <sup>2</sup> ), i.e. 10 ml/m <sup>2</sup> .
<b>Drying time</b>	At 23° C (73 °F) and 50% relative humidity, approximately 2 - 4 hours.
<b>Cleaning</b>	Clean equipment immediately after use with SVALOS Thinner No. 222, or LEVO Brush Cleaner No. 997.
<b>Specific gravity</b>	0.78 g/ml.
<b>Safety advice</b>	Ensure good ventilation during and after application. P102 Keep out of reach of children. P301+P310 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a doctor. EUH066 Repeated exposure may cause skin dryness or cracking. EUH208 Contains limonene (orange oil). May produce an allergic reaction.
<b>Disposal</b>	According to locally regulated laws.
<b>Container sizes</b>	0.25 l; 1 l; 2.5 l; 10 l; 30 l; 200 l.
<b>Storage</b>	Cool and dry. Shelf life: unopened at least 4 years. Close lid tightly after use.
<b>Packaging</b>	Made of polyethylene (PE). This material is ground water neutral and recyclable.  See reverse for application instructions.

How to use

## **GLEIVO Beeswax No. 315**

- Preparation** The surface must be dry, solid, clean, and free of grease and dust. Pre-treatment with LIVOS oils, e.g. MELDOS Natural Resin Hardening Oil No. 264, ARDVOS Universal Wood Oil No. 266 or LIVOS stains, such as DARIX Transparent Furniture Stain No. 297.  
To ensure compatibility on surfaces previously treated with products from another manufacturer, do a test application on an inconspicuous area.
- Application** Before use, shake or stir product well.  
Apply GLEIVO Beeswax No. 315 very thin and evenly with a brush or cloth. After approximately 2 - 4 hours, polish (wood in the direction of the wood grain) with a wadded cloth, wax brush or single disc rotary machine or random orbital sander and felt pad.
- Cleaning** Remove dust with a vacuum cleaner or mop.  
Rubber abrasion and stubborn dirt can be removed with SVALOS Thinner No. 222 or with a saturated application of beeswax. Clean with TRENA pH-Neutral Cleaner No. 556 diluted in water according to demand.
- Care** According to usage, apply an after-treatment with GLEIVO Beeswax No. 315 once or twice a year.
- Important tips** Ensure good ventilation during application and drying times.  
Too thick application needs an intensive mechanical polishing. Strong electrostatic charge e.g. of a synthetic paint etc. will be reduced or eliminated by a very thin coating of the beeswax.
- On surfaces coated with DELVA Smooth Render No. 426, GLEIVO No. 315 protects against abrasion and dirt. GLEIVO delays the possible fading of DELVA admixed plant pigments / mixtures and imparts a brilliant, satin gloss.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at [www.livos.de](http://www.livos.de). This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

January 2016