




Technical Data Sheet

TEKNO Oil & Wax Remover No. 539

Application range	In the interior, for sticky, not properly dried, to thickly applied oil or wax layers.
Technical qualities	Removes dirt, grease, fat, waxes, polymer waxes, plant- and mineral oils, with stripping effect. pH-value = 12.3.
Full declaration	Water, orange oil, mixture out of anionic, non-ionic and amphoteric surfactants based on natural raw materials, sugar – fatty acid – condensate and glycerol.
Color	Yellowish brown.
Dilution	Depending on the degree of soiling, dilute with water in the ratio 1:5 up to 1:10.
Application method	Shake well before use. Apply by spraying, dipping or with a brush (see reverse side for further information).
Cleaning	Clean equipment immediately after use with water.
Specific gravity	Approximately 1.04 g/ml.
Safety advice	<p>Ensure good ventilation during and after application.</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 10px;">    </div> <div> <p>H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects. P102 Keep out of reach of children. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/ face protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P405 Store locked up.</p> </div> </div> <p>Danger</p> <p>Anionic surfactants: > 5%, non-ionic surfactants: > 5%. Surfactants are readily biodegradable (according to OECD criteria). Always do a test application for compatibility and efficiency on the surface to be treated.</p>
Disposal	According to locally regulated laws.
Container sizes	0.5 l, 1 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years.
Packaging	Made of polyethylene (PE). This material is ground water neutral and recyclable. See reverse for application instructions.

How to use

TEKNO Oil & Wax Remover No. 539

Application

Shake well before use.

Dilute TEKNO Oil & Wax Remover with 5 - 10 parts of water und apply it with a sponge or brush onto the surface to be treated; leave to react for 20 to 30 minutes (wood 5 - 10 minutes). When working with a single disc rotary machine, use a pad of 120 grain (e.g. green pad), an abrasive fleece or a scrub sponge to soften the sticky layer. Remove the material and wipe at least twice with clear water until the water is pH-neutral and clear. If you work selectively on a surface, the surrounding area must be protected by taping. Protect adjacent untreated wood from contact! After drying, all treated surfaces must be gradually finely sanded, minimum up to 120 grain!

After-treatment:

Use LIVOS oils, e.g. ARDVOS Universal Wood Oil No. 266 or other suitable LIVOS products like the KUNOS Oils No. 242 - 245.

Important tips

The reaction time depends on the degree, density and the age of soiling.

Using the support of mechanical tools (brush, sponge, pad) and hot water speeds up the cleaning process and produces excellent results.

To reach a homogeneous new coating the floor must be sanded carefully, otherwise stains might appear.

Before using, do a test application for compatibility and efficiency on an inconspicuous area.

Discoloration can be caused with woods containing tannic acids (e.g. oak).

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

February 2016 Rev 2.5