


Technical Data Sheet

LATIS Tool Cleaner No. 558

Range of application	For brushes and rollers after working with LIVOS water soluble coatings.
Technical qualities	Alkaline. Removes resins and oily dirt out of painter's tools.
Full declaration	Water, potassium soaps of corn germ oil, potassium hydroxide, ethanol and rosemary oil.
Color	Clear.
Application method	Dilute Cleaner with 1 - 2 parts of water. Soak tools in this solution for 2 minutes, let bristles soften and rinse with clear water. Depending on the grade of soiling repeat the procedure. Very soiled brushes and sponges should be soaked 0.5 - 2 hours.
Specific gravity	Ca. 1,0 g/ml.
Safety advice	Rinse off splashes to eyes or mucous membranes immediately with plenty of water. Anionic Surfactants: > 15% Fragrances: < 5%
	<p style="text-align: center;">Xi</p> <div style="display: flex; align-items: center;">  <div style="margin-left: 10px;"> <p>R 36 Irritating to eyes.</p> <p>R 38 Irritating to skin.</p> <p>S 2 Keep out of the reach of children.</p> <p>S 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.</p> </div> </div> <p style="text-align: center;">Irritant</p>
Disposal	According to locally regulated laws.
Container Sizes	0.5 l; 2.5 l; 30 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years.
Packaging	Polyethylene (PE). This material is groundwater-neutral and recyclable.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

August 2012